

**គ្រប់មេខ័ែ ( Incubator ) Model. CLN 240 , CLW 240 “ POL-EKO POLAND ”**



<b>chamber capacity <sup>1</sup> [l]</b>	245
<b>TEMPERATURE</b>	
<b>temperature range [°C]</b>	+5°C above ambient temperature... +100°C
<b>temperature resolution [°C]</b>	every 0,1
<b>temperature fluctuation<sup>3</sup> [°C]</b>	CLN / CLW
at 37°C	+/- 0,1 / 0,1
at 44°C	+/- 0,2 / 0,1
<b>temperature variation<sup>4</sup> [°C]</b>	
at 37°C	+/- 1,1 / 0,6
at 44°C	+/- 1,4 / 0,6
<b>over temperature protection</b>	class 2.0 to DIN 12880/ class 3.1 (option)/ class 3.1 in TOP+ version
<b>interior</b>	acid-proof stainless steel to DIN 1.4301
<b>housing</b>	
-	powder coated sheet
INOX/G	stainless steel linen finish
<b>door type</b>	solid/ door with viewing window (option)
<b>controller</b>	microprocessor with external LCD graphic display
<b>shelves fitted</b>	3
<b>ELECTRICAL PARAMETERS</b>	
<b>voltage</b>	230V 50Hz 800W